

BREAK SHARP CORNERS MAY BE EITHER CHAMFER OR RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.

THIS DRAWING IS A SOLE PROPERTY OF M & M Ltd. IT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THEIR CONSENT

D

C

B

A

D


C

B

A

REFER DRAWING :- 007537394C91

REF PART NO: 007537394C91

UNSPECIFIED TOLERANCES AS PER ISO-2768-1:1989 (DIMENSION)											SURFACE FINISH SYMBOLS:ISO-1302		 MAHINDRA & MAHINDRA LTD. FARM DIVISION, INDIA								
LINEAR IN mm.		OVER	0.5	3	6	30	120	400	1000	2000	WELDING SYMBOLS:IS813										
		UPTO	3	6	30	120	400	1000	2000	4000	REMOVE ALL SHARP CORNERS & BURRS										
f	FINE (X.XXX)		±0.05	±0.05	±0.1	±0.15	±0.2	±0.3	±0.5	-	DO NOT SCALE ALL DIMENSIONS ARE IN mm	<SC> COUNT : 0		NAME		DATE	PROJECT CODE:				
m	MEDIUM (X.XX)		±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2		<CC> COUNT : 0		DSNR	AR	07-06-2023	ER NUMBER: ER23C0000228				
c	COARSE (X.X)		±0.2	±0.3	±0.5	±0.8	±1.2	±2	±3	±4		WEIGHT(kg) : 0.04		CHKR	NVC	07-06-2023	DESCRIPTION :				
v	VERY COARSE (X)			±0.5	±1	±1.5	±2.5	±4	±6	±8		S/F AREA(cm²): 22		APPR	DS	07-06-2023	PIN PARKING BRAKE LEVER MTG				
ANGULAR IN deg.		LENGTH OF SHORTER SIDE OF THE ANGLE IN mm.										MATERIAL:		PART NUMBER :				CL:			
		OVER		-		10		50		120		400		 DWG.SIZE : A4				SCALE : 2:1		SHEET: 1 OF 1	
				UPTO		10		50		120		400									
f	FINE (X.XXX)		±1°			±0°30'		±0°20'		±0°10'		±0°5'									
m	MEDIUM (X.XX)		±1°30'		±1°		±0°30'		±0°15'		±0°10'										
c	COARSE (X.X)		±3°		±2°		±1°		±0°30'		±0°20'										
v	VERY COARSE (X)																				